

Material Safety Data Sheet

AMSOIL Synthetic Fifth-Wheel Grease

Code

Section 1. Product and company identification

Date : 08/15/2012

Version: 1

Product name

AMSOIL Synthetic Fifth-Wheel Grease

Material uses
Lubricating Grease.

Supplier/Manufacturer

AMSOIL INC. 925 Tower Avenue Superior, WI 54880 FWG MSDS authored by

AMSOIL INC.

In case of emergency

CHEMTREC, U.S.: 1-800-424-9300 International: +1-703-527-3887

Section 2. Hazards identification

Emergency overview

Color : Gray. [Dark]
Physical state : Grease.
Odor : Mild (Faint.)
Signal word : WARNING!

Hazard statements : CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Precautions: Do not get in eyes. Avoid contact with skin and clothing. Wash thoroughly after

handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Skin : May cause skin irritation.

Eyes : Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects

Chronic effects
 Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation: No specific data.Ingestion: No specific data.

Skin: Adverse symptoms may include the following:

irritation redness

1/7 Date of issue : 08/15/2012

10 - 20

3 - 7

Eyes: Adverse symptoms may include the following:

pain or irritation watering

Medical conditions aggravated by overexposure

Calcium carbonate

Molybdenum sulfide

redness
: None known.

See toxicological information (Section 11)

Section 3. Composition/information on ingredients

United States		
Name	CAS number	%
Mineral oil.	Not available.	20 - 40
Calcium carbonate	471-34-1	10 - 20
Molybdenum sulfide	1317-33-5	3 - 7
Canada		
Name	CAS number	%
Mineral oil.	Not available.	20 - 40

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

Eye contact	:	Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting
		the upper and lower evelids

Skin contact: After contact with skin, wash immediately with plenty of soap and water. Get medical attention if symptoms occur.

Inhalation : Move exposed person to fresh air. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 5. Fire-fighting measures

Flammability of the product : No specific fire or explosion hazard.

Extinguishing media

Suitable : Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable : None known.

Hazardous decomposition : Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide sulfur oxides nitrogen oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

471-34-1

1317-33-5

2/7 Date of issue : 08/15/2012

Section 6. Accidental release measures

Personal precautions

: Provide adequate ventilation. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

Large spill

- : Absorb with an inert dry material and place in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor.
- : Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Avoid contact with used product. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
Calcium carbonate	OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m³ 8 hour(s). Form: Total dust ACGIH TLV (United States, 11/2006). TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m³ 8 hour(s). Form: Total dust
Molybdenum sulfide	ACGIH TLV (United States, 2/2010). TWA: 10 mg/m³, (as Mo) 8 hour(s). Form: Inhalable fraction. TWA: 3 mg/m³, (as Mo) 8 hour(s). Form: Respirable fraction OSHA PEL (United States, 6/2010). TWA: 15 mg/m³, (as Mo) 8 hour(s). Form: Total dust OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m³, (as Mo) 8 hour(s). Form: Total dust

Under conditions which may generate mists, the following additional exposure limits are recommended: ACGIH TLV TWA: 5 mg/m³; STEL: 10 mg/m³.

Canada

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)		Ceiling					
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Molybdenum sulfide, as Mo	US ACGIH 2/2010	-	10 3	-	-	-	-	-	-	-	[a] [b]
	AB 4/2009	-	10 3	-	-	-	-	-	-	-	[c]
Molybdenum sulfide	BC 9/2010	-	10 3	-	-	-	-	-	-	-	[d] [c]
Molybdenum sulfide, as Mo	ON 7/2010	-	10 3	-	-	-	-	-	-	-	[a] [b]
Calcium carbonate	QC 6/2008 US ACGIH 11/2006	-	10 5	-	-	-	-	-	-	-	[b]
	AB 4/2009	-	15 10	-	-	-	-	-	-	-	[e] [3]
	QC 6/2008	-	10	-	-	-	-	-	-	-	[e]

[3]Skin sensitization

Form: [a]Inhalable fraction. [b]Respirable fraction [c]Respirable. [d]Inhalable [e]Total dust

Under conditions which may generate mists, the following additional exposure limits are recommended: ACGIH TLV TWA: 5 mg/m³; STEL: 10 mg/m³.

Consult local authorities for acceptable exposure limits.

Recommended	monitoring
procedures	

: Personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: No special ventilation requirements. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Respiratory

: Not required under normal conditions of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure a MSHA/NIOSH-approved respirator or equivalent is used.

Hands

: Use gloves appropriate for work or task being performed. Recommended: Natural rubber (latex).

Eyes

: Safety eyewear should be used when there is a likelihood of exposure. Recommended: Safety glasses with side shields.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. No special protective clothing is required. Recommended: Coveralls.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Section 9. Physical and chemical properties

Physical state: Grease.Odor: Mild (Faint.)Color: Gray. [Dark]pH: Not available.Flash point: Not available.Auto-ignition: Not available.

Flammable limits : Not available. temperature

Melting point/ : Not available.

Pour point

Boiling point: Not available. **Vapor pressure**: Not available. **Relative density**: 0.97 **Vapor density**: Not available.

Date of issue: 08/15/2012

Volatility : Not available. **Evaporation rate** : Not available. **Viscosity** : Not available. **Solubility** : Insoluble

Section 10. Stability and reactivity

Chemical stability

: The product is stable.

Conditions to avoid

: No specific data.

Materials to avoid

: Reactive or incompatible with the following materials: oxidizing materials and acids.

Hazardous decomposition

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

products

Possibility of hazardous

: Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Molybdenum sulfide Calcium carbonate			>2820 mg/m³ 6450 mg/kg	4 hours

Chronic toxicity

There is no data available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Calcium carbonate	Eyes - Severe irritant	Rabbit	-	24 hours 750	-
	Skin - Moderate irritant	Rabbit	-	µg 24 hours 500 mg	-

Sensitizer

: There is no data available. Skin Respiratory : There is no data available.

Carcinogenicity

There is no data available.

Mutagenicity

There is no data available.

Teratogenicity

There is no data available.

Reproductive toxicity

There is no data available.

Date of issue : 08/15/2012 5/7

Section 12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
	Acute LC50 >56000000 ug/L Fresh water Chronic NOEC 61 mg/g Fresh water	Fish - Gambusia affinis - Adult Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours 28 days

Persistence/degradability

There is no data available.

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. This material and its container must be disposed of in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Empty containers or liners may retain some product residues. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

6/7

Section 14. Transport information

DOT/TDG/IMDG/IATA : Not regulated.

Section 15. Regulatory information

United States

HCS Classification

: Irritating material

U.S. Federal regulations

: United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Overbased calcium sulfonate complex

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Overbased calcium sulfonate complex thickener: Immediate (acute) health hazard

Clean Air Act Section 112(b) Hazardous Air **Pollutants (HAPs)**

: Not listed

Clean Air Act Section 602 : Not listed

Class I Substances

Clean Air Act Section 602 : Not listed

Class II Substances

Date of issue : 08/15/2012 **DEA List I Chemicals**

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

(Essential Chemicals)

: Not listed

State regulations

Massachusetts : The following components are listed: Molybdenum sulfide

New York : None of the components are listed.

New Jersey : None of the components are listed.

Pennsylvania : None of the components are listed.

California Prop. 65

No products were found.

Canada

WHMIS (Canada) : Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : None of the components are listed.
 CEPA Toxic substances : None of the components are listed.
 Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Section 16. Other information

United States

Label requirements : CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Date of issue : 08/15/2012

Version : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue : 08/15/2012