



## Material Safety Data Sheet

### Diesel Concentrate Performance Fuel Additive

## Section 1. Product and company identification

### Product name

Diesel Concentrate Performance Fuel Additive

### Material uses

Fuel additive.

### Supplier/Manufacturer

AMSOIL INC.  
925 Tower Avenue  
Superior, WI 54880

### Code

ADF

### MSDS authored by

AMSOIL INC.

### In case of emergency

CHEMTREC: (800) 424-9300

## Section 2. Hazards identification

### Emergency overview

- Color** : Brown.
- Physical state** : Liquid. [Fluid.]
- Odor** : Aromatic hydrocarbon.
- Signal word** : WARNING!
- Hazard statements** : COMBUSTIBLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL OR FATAL IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER. POSSIBLE DEVELOPMENTAL HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE ADVERSE DEVELOPMENTAL EFFECTS, BASED ON ANIMAL DATA.
- Precautions** : Keep away from heat, sparks and flame. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid exposure during pregnancy. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
- OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- Potential acute health effects**
  - Inhalation** : Irritating to respiratory system.
  - Ingestion** : Harmful or fatal if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.
  - Skin** : Irritating to skin. May be harmful in contact with skin.
  - Eyes** : Irritating to eyes.
- Potential chronic health effects**
  - Chronic effects** : Contains material that can cause target organ damage.
  - Carcinogenicity** : Contains material which may cause cancer. Risk of cancer depends on duration and level of exposure.
  - Mutagenicity** : No known significant effects or critical hazards.
  - Teratogenicity** : No known significant effects or critical hazards.
  - Developmental effects** : Contains material which may cause developmental abnormalities, based on animal data.

- Fertility effects** : No known significant effects or critical hazards.
- Target organs** : Contains material which may cause damage to the following organs: blood, kidneys, lungs, liver, gastrointestinal tract, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

**Over-exposure signs/symptoms**

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced fetal weight  
increase in fetal deaths
- Skin** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness  
reduced fetal weight  
increase in fetal deaths
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

## Section 3. Composition/information on ingredients

### United States

| Name  | CAS number | %       |
|---|------------|---------|
| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 30 - 60 |
| 1,2,4-Trimethylbenzene                      | 95-63-6    | 30 - 60 |
| Solvent naphtha (petroleum), heavy aromatic | 64742-94-5 | 10 - 30 |
| Mesitylene                                  | 108-67-8   | 5 - 10  |
| Benzene, diethyl-                           | 25340-17-4 | 1 - 5   |
| Cumene                                      | 98-82-8    | 1 - 5   |
| Xylene                                      | 1330-20-7  | 1 - 5   |
| Naphthalene                                 | 91-20-3    | 1 - 5   |

### Canada

| Name  | CAS number | %       |
|---|------------|---------|
| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 30 - 60 |
| 1,2,4-Trimethylbenzene                      | 95-63-6    | 30 - 60 |
| Solvent naphtha (petroleum), heavy aromatic | 64742-94-5 | 10 - 30 |
| Mesitylene                                  | 108-67-8   | 5 - 10  |
| Benzene, diethyl-                           | 25340-17-4 | 1 - 5   |
| Cumene                                      | 98-82-8    | 1 - 5   |
| Xylene                                      | 1330-20-7  | 1 - 5   |
| Naphthalene                                 | 91-20-3    | 1 - 5   |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

---

## Section 4. First aid measures

---

- Eye contact** : Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.
- Skin contact** : After contact with skin, wash immediately with plenty of soap and water. Get medical attention if symptoms occur.
- Inhalation** : Move exposed person to fresh air. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call medical doctor or poison control center immediately.
- Protection of first-aiders** : If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

---

## Section 5. Fire-fighting measures

---

- Flammability of the product** : Combustible liquid.
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

---

## Section 6. Accidental release measures

---

- Personal precautions** : Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Hazardous to aquatic environment May cause long-term adverse effects in the aquatic environment. Prevent leaking substances from running into the aquatic environment or the sewage system.
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

- Large spill** : Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## Section 7. Handling and storage

- Handling** : Put on appropriate personal protective equipment. Avoid contact with used product. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### United States

| Ingredient                                  | Exposure limits   |
|---|---|
| Solvent naphtha (petroleum), light aromatic | <b>Manufacturer (United States).</b><br>TWA: 40 ppm 8 hour(s).  |
| 1,2,4-Trimethylbenzene                      | <b>ACGIH TLV (United States, 2/2010).</b><br>TWA: 123 mg/m <sup>3</sup> 8 hour(s).<br>TWA: 25 ppm 8 hour(s).  |
|   | <b>NIOSH REL (United States, 6/2009).</b><br>TWA: 125 mg/m <sup>3</sup> 10 hour(s).<br>TWA: 25 ppm 10 hour(s).  |
|   | <b>OSHA PEL 1989 (United States, 3/1989).</b><br>TWA: 25 ppm 8 hour(s).<br>TWA: 125 mg/m <sup>3</sup> 8 hour(s).  |
| Mesitylene                                  | <b>ACGIH TLV (United States, 2/2010).</b><br>TWA: 123 mg/m <sup>3</sup> 8 hour(s).<br>TWA: 25 ppm 8 hour(s).  |
|   | <b>NIOSH REL (United States, 6/2009).</b><br>TWA: 125 mg/m <sup>3</sup> 10 hour(s).<br>TWA: 25 ppm 10 hour(s).  |
|   | <b>OSHA PEL 1989 (United States, 3/1989).</b><br>TWA: 25 ppm 8 hour(s).<br>TWA: 125 mg/m <sup>3</sup> 8 hour(s).  |
| Benzene, diethyl-                           | <b>AIHA WEEL (United States, 5/2010).</b><br>TWA: 5 ppm 8 hour(s).  |
| Cumene                                      | <b>ACGIH TLV (United States, 2/2010).</b><br>TWA: 50 ppm 8 hour(s).   |
|   | <b>NIOSH REL (United States, 6/2009). Absorbed through skin.</b><br>TWA: 245 mg/m <sup>3</sup> 10 hour(s).<br>TWA: 50 ppm 10 hour(s).   |
|   | <b>OSHA PEL (United States, 6/2010). Absorbed through skin.</b><br>TWA: 245 mg/m <sup>3</sup> 8 hour(s).<br>TWA: 50 ppm 8 hour(s).  |
| Xylene                                      | <b>ACGIH TLV (United States, 2/2010).</b><br>STEL: 651 mg/m <sup>3</sup> 15 minute(s).<br>STEL: 150 ppm 15 minute(s).<br>TWA: 434 mg/m <sup>3</sup> 8 hour(s).<br>TWA: 100 ppm 8 hour(s). |

|             |   |
|-------------|---|
| Naphthalene | <p><b>OSHA PEL (United States, 6/2010).</b><br/>TWA: 435 mg/m<sup>3</sup> 8 hour(s).<br/>TWA: 100 ppm 8 hour(s).</p> <p><b>ACGIH TLV (United States, 2/2010).</b><br/>STEL: 79 mg/m<sup>3</sup> 15 minute(s).<br/>STEL: 15 ppm 15 minute(s).<br/>TWA: 52 mg/m<sup>3</sup> 8 hour(s).<br/>TWA: 10 ppm 8 hour(s).</p> <p><b>NIOSH REL (United States, 6/2009).</b><br/>STEL: 75 mg/m<sup>3</sup> 15 minute(s).<br/>STEL: 15 ppm 15 minute(s).<br/>TWA: 50 mg/m<sup>3</sup> 10 hour(s).<br/>TWA: 10 ppm 10 hour(s).</p> <p><b>OSHA PEL (United States, 6/2010).</b><br/>TWA: 50 mg/m<sup>3</sup> 8 hour(s).<br/>TWA: 10 ppm 8 hour(s).</p> |
|-------------|---|

**Canada**

| Occupational exposure limits |                 | TWA (8 hours) |                   |       | STEL (15 mins) |                   |       | Ceiling |                   |       |           |
|------------------------------|-----------------|---------------|-------------------|-------|----------------|-------------------|-------|---------|-------------------|-------|-----------|
| Ingredient                   | List name       | ppm           | mg/m <sup>3</sup> | Other | ppm            | mg/m <sup>3</sup> | Other | ppm     | mg/m <sup>3</sup> | Other | Notations |
| 1,2,4-Trimethylbenzene       | US ACGIH 2/2010 | 25            | 123               | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | AB 4/2009       | 25            | 123               | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | BC 9/2010       | 25            | -                 | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | ON 7/2010       | 25            | 123               | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | QC 6/2008       | 25            | 123               | -     | -              | -                 | -     | -       | -                 | -     |           |
| Mesitylene                   | US ACGIH 2/2010 | 25            | 123               | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | AB 4/2009       | 25            | 123               | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | BC 9/2010       | 25            | -                 | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | ON 7/2010       | 25            | 123               | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | QC 6/2008       | 25            | 123               | -     | -              | -                 | -     | -       | -                 | -     |           |
| Benzene, diethyl-Cumene      | US AIHA 5/2010  | 5             | -                 | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | US ACGIH 2/2010 | 50            | -                 | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | AB 4/2009       | 50            | 246               | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | BC 9/2010       | 25            | -                 | -     | 75             | -                 | -     | -       | -                 | -     |           |
|                              | ON 7/2010       | 50            | -                 | -     | -              | -                 | -     | -       | -                 | -     | [1]       |
| Xylene                       | QC 6/2008       | 50            | 246               | -     | -              | -                 | -     | -       | -                 | -     |           |
|                              | US ACGIH 2/2010 | 100           | 434               | -     | 150            | 651               | -     | -       | -                 | -     |           |
|                              | AB 4/2009       | 100           | 434               | -     | 150            | 651               | -     | -       | -                 | -     |           |
|                              | BC 9/2010       | 100           | -                 | -     | 150            | -                 | -     | -       | -                 | -     |           |
|                              | ON 7/2010       | 100           | 434               | -     | 150            | 651               | -     | -       | -                 | -     |           |
| Naphthalene                  | QC 6/2008       | 100           | 434               | -     | 150            | 651               | -     | -       | -                 | -     |           |
|                              | US ACGIH 2/2010 | 10            | 52                | -     | 15             | 79                | -     | -       | -                 | -     |           |
|                              | AB 4/2009       | 10            | 52                | -     | 15             | 79                | -     | -       | -                 | -     | [1]       |
|                              | BC 9/2010       | 10            | -                 | -     | 15             | -                 | -     | -       | -                 | -     | [1]       |
|                              | ON 7/2010       | 10            | 52                | -     | 15             | 79                | -     | -       | -                 | -     |           |
| QC 6/2008                    | 10              | 52            | -                 | 15    | 79             | -                 | -     | -       | -                 |       |           |

[1]Absorbed through skin.

**Consult local authorities for acceptable exposure limits.**

**Recommended monitoring procedures** : Personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

**Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Use explosion-proof ventilation equipment.

**Hygiene measures** : Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

**Respiratory** : Not required under normal conditions of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure an MSHA/NIOSH-approved respirator or equivalent is used.

**Hands** : Use gloves appropriate for work or task being performed. Recommended: Natural rubber (latex).

- Eyes** : Safety eyewear should be used when there is a likelihood of exposure. Recommended: Safety glasses with side shields.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. No special protective clothing is required. Recommended: Coveralls.
- Environmental exposure controls** : In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## Section 9. Physical and chemical properties

- |                         |  |                                  |                         |
|-------------------------|--|----------------------------------|-------------------------|
| <b>Physical state</b>   | : Liquid. [Fluid.]                                     | <b>Odor</b>                      | : Aromatic hydrocarbon. |
| <b>Color</b>            | : Brown.   | <b>pH</b>                        | : Not available.        |
| <b>Flash point</b>      | : Closed cup: 47°C (116.6°F) [Pensky-Martens.]         | <b>Auto-ignition temperature</b> | : Not available.        |
| <b>Flammable limits</b> | : Not available.                                       | <b>Melting point/ Pour point</b> | : -53°C (-63.4°F)       |
| <b>Boiling point</b>    | : Not available.                                       | <b>Vapor pressure</b>            | : Not available.        |
| <b>Relative density</b> | : 0.8866   | <b>Vapor density</b>             | : Not available.        |
| <b>Volatility</b>       | : Not available.                                       | <b>Evaporation rate</b>          | : Not available.        |
| <b>Viscosity</b>        | : Kinematic: 0.014 cm <sup>2</sup> /s (1.4 cSt) (40°C) | <b>Solubility</b>                | : Not available.        |

## Section 10. Stability and reactivity

- Chemical stability** : The product is stable.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Materials to avoid** : Reactive or incompatible with the following materials: oxidizing materials, combustible materials and alkalis.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

## Section 11. Toxicological information

### Acute toxicity

| Product/ingredient name                     | Result                | Species    | Dose                    | Exposure |
|---|-----------------------|------------|-------------------------|----------|
| Solvent naphtha (petroleum), light aromatic | LD50 Oral             | Rat        | 8400 mg/kg              | -        |
| 1,2,4-Trimethylbenzene                      | LC50 Inhalation Vapor | Rat        | 18000 mg/m <sup>3</sup> | 4 hours  |
|   | LD50 Oral             | Rat        | 5 g/kg                  | -        |
| Solvent naphtha (petroleum), heavy aromatic | LC50 Inhalation Vapor | Rat        | >590 mg/m <sup>3</sup>  | 4 hours  |
|   |                       | Mesitylene | LC50 Inhalation Vapor   | Rat      |
| Benzene, diethyl-                           | LD50 Oral             | Rat        | 5000 mg/kg              | -        |
|   | LD50 Dermal           | Rabbit     | >5000 mg/kg             | -        |
|   | LD50 Dermal           | Rat        | >2000 mg/kg             | -        |
| Cumene                                      | LD50 Oral             | Rat        | 2050 mg/kg              | -        |
|   | LC50 Inhalation Vapor | Rat        | 39000 mg/m <sup>3</sup> | 4 hours  |
|   | LD50 Oral             | Rat        | 1400 mg/kg              | -        |
| Xylene                                      | LC50 Inhalation Gas.  | Rat        | 5000 ppm                | 4 hours  |

|             |             |        |             |   |
|-------------|-------------|--------|-------------|---|
| Naphthalene | LD50 Dermal | Rabbit | >1700 mg/kg | - |
|             | LD50 Oral   | Rat    | 4300 mg/kg  | - |
|             | LD50 Dermal | Rabbit | >20 g/kg    | - |
|             | LD50 Dermal | Rat    | >2500 mg/kg | - |
|             | LD50 Oral   | Rat    | 490 mg/kg   | - |

**Chronic toxicity****Classification**

| Product/ingredient name | ACGIH | IARC | EPA | NIOSH | NTP      | OSHA |
|-------------------------|-------|------|-----|-------|----------|------|
| Xylene                  | A4    | 3    | -   | -     | -        | -    |
| Naphthalene             | A4    | 2B   | -   | None. | Possible | -    |

**Section 12. Ecological information**

**Environmental effects** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Aquatic ecotoxicity**

| Product/ingredient name | Result                                     | Species   | Exposure |
|-------------------------|--|---|----------|
| 1,2,4-Trimethylbenzene  | Acute LC50 17000 ug/L Marine water         | Crustaceans - Cancer magister - Zoea                                | 48 hours |
| Mesitylene              | Acute LC50 7720 to 8280 ug/L Fresh water   | Fish - Pimephales promelas - 34 days                                | 96 hours |
|                         | Acute LC50 13000 ug/L Marine water         | Crustaceans - Cancer magister - Zoea                                | 48 hours |
| Cumene                  | Acute LC50 12520 to 15050 ug/L Fresh water | Fish - Carassius auratus - 1 to 15 years - 13 to 20 cm - 20 to 80 g | 96 hours |
|                         | Acute EC50 2600 ug/L Fresh water           | Algae - Pseudokirchneriella subcapitata                             | 72 hours |
| Xylene                  | Acute EC50 11200 ug/L Fresh water          | Daphnia - Daphnia magna - Neonate - <=24 hours                      | 48 hours |
|                         | Acute LC50 7400 ug/L Fresh water           | Crustaceans - Artemia sp. - Nauplii                                 | 48 hours |
|                         | Acute LC50 2700 ug/L Fresh water           | Fish - Oncorhynchus mykiss  | 96 hours |
|                         | Acute IC50 10 mg/L                         | Algae   | 72 hours |
| Naphthalene             | Acute LC50 8500 ug/L Marine water          | Crustaceans - Palaemonetes pugio                                    | 48 hours |
|                         | Acute LC50 3300 to 4093 ug/L Fresh water   | Fish - Oncorhynchus mykiss - 0.6 g                                  | 96 hours |
|                         | Acute EC50 1600 ug/L Fresh water           | Daphnia - Daphnia magna - Neonate - <=24 hours                      | 48 hours |
|                         | Acute LC50 2350 ug/L Marine water          | Crustaceans - Palaemonetes pugio                                    | 48 hours |
|                         | Acute LC50 213 ug/L Fresh water            | Fish - Melanotaenia fluviatilis - Larvae - 1 days                   | 96 hours |
|                         | Chronic NOEC 600 ug/L Fresh water          | Daphnia - Daphnia magna - <=24 hours                                | 48 hours |





**Section 13. Disposal considerations**

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. This material and its container must be disposed of in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Empty containers or liners may retain some product residues. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## Section 14. Transport information

| Regulatory information    | UN number | Proper shipping name  | Classes | PG* | Label   | Additional information |
|---------------------------|-----------|---|---------|-----|---|------------------------|
| <b>DOT Classification</b> | UN1268    | PETROLEUM DISTILLATES, N.O.S. (Solvent naphtha (petroleum), heavy aromatic, 1,2,4-Trimethylbenzene) | 3       | II  |  | -                      |
| <b>TDG Classification</b> | UN1268    | PETROLEUM DISTILLATES, N.O.S. (Solvent naphtha (petroleum), heavy aromatic, 1,2,4-Trimethylbenzene) | 3       | II  |  | -                      |
| <b>IMDG Class</b>         | UN1268    | PETROLEUM DISTILLATES, N.O.S. (Solvent naphtha (petroleum), heavy aromatic, 1,2,4-Trimethylbenzene) | 3       | II  |  | -                      |
| <b>IATA-DGR Class</b>     | UN1268    | PETROLEUM DISTILLATES, N.O.S. (Solvent naphtha (petroleum), heavy aromatic, 1,2,4-Trimethylbenzene) | 3       | II  |  | -                      |

PG\* : Packing group

Exemption to the above classification may apply.

AERG : 128

## Section 15. Regulatory information

### United States

**HCS Classification** : Combustible liquid  
Toxic material  
Irritating material  
Carcinogen  
Target organ effects

**U.S. Federal regulations** : **United States inventory (TSCA 8b)**: All components are listed or exempted.  
**SARA 302/304/311/312 extremely hazardous substances**: No products were found.  
**SARA 302/304 emergency planning and notification**: No products were found.  
**SARA 302/304/311/312 hazardous chemicals**: 1,2,4-Trimethylbenzene; Mesitylene; Benzene, diethyl-; Cumene; Xylene; Naphthalene  
**SARA 311/312 MSDS distribution - chemical inventory - hazard identification**:  
1,2,4-Trimethylbenzene: Fire hazard, Delayed (chronic) health hazard; Mesitylene: Fire hazard, Immediate (acute) health hazard; Benzene, diethyl-: Fire hazard, Immediate (acute) health hazard; Cumene: Fire hazard, Immediate (acute) health hazard; Xylene: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard; Naphthalene: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard  
**Clean Water Act (CWA) 307**: Naphthalene  
**Clean Water Act (CWA) 311**: Xylene; Naphthalene  
**Clean Air Act (CAA) 112 accidental release prevention**: No products were found.



**SARA 313**

|  | <u>Product name</u>      | <u>CAS number</u> | <u>Concentration</u> |
|--|--------------------------|-------------------|----------------------|
| <b>Form R - Reporting requirements</b> | : 1,2,4-Trimethylbenzene | 95-63-6           | 30 - 60              |
|  | Cumene                   | 98-82-8           | 1 - 5                |
|  | Xylene                   | 1330-20-7         | 1 - 5                |
|  | Naphthalene              | 91-20-3           | 1 - 5                |
| <b>Supplier notification</b>           | : 1,2,4-Trimethylbenzene | 95-63-6           | 30 - 60              |
|  | Cumene                   | 98-82-8           | 1 - 5                |
|  | Xylene                   | 1330-20-7         | 1 - 5                |
|  | Naphthalene              | 91-20-3           | 1 - 5                |

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

**State regulations**

- Massachusetts** : The following components are listed: 1,2,4-Trimethylbenzene; Mesitylene; Cumene; Xylene; Naphthalene
- New York** : The following components are listed: Cumene; Xylene; Naphthalene
- New Jersey** : The following components are listed: 1,2,4-Trimethylbenzene; Mesitylene; Benzene, diethyl-; Cumene; Xylene; Naphthalene
- Pennsylvania** : The following components are listed: 1,2,4-Trimethylbenzene; Mesitylene; Cumene; Xylene; Naphthalene

**California Prop. 65**

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

| <u>Ingredient name</u> | <u>Cancer</u> | <u>Reproductive</u> | <u>No significant risk level</u> | <u>Maximum acceptable dosage level</u> |
|------------------------|---------------|---------------------|----------------------------------|--|
| Cumene                 | Yes.          | No.                 | No.                              | No.                                    |
| Naphthalene            | Yes.          | No.                 | Yes.                             | No.                                    |

**Canada**

- WHMIS (Canada)** : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).  
Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).
- Canadian lists** : **CEPA Toxic substances:** The following components are listed: Naphthalene  
**Canadian ARET:** None of the components are listed.  
**Canadian NPRI:** The following components are listed: Solvent naphtha (petroleum), light aromatic; 1,2,4-Trimethylbenzene; Mesitylene; Cumene; Xylene; Solvent naphtha (petroleum), heavy aromatic; Naphthalene  
**Alberta Designated Substances:** None of the components are listed.  
**Ontario Designated Substances:** None of the components are listed.  
**Quebec Designated Substances:** None of the components are listed.
- Canada inventory** : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**International regulations**

- International lists** : **Australia inventory (AICS):** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Japan inventory:** Not determined.  
**Korea inventory:** All components are listed or exempted.  
**New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.

## Section 16. Other information

### United States

**Label requirements** : COMBUSTIBLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL OR FATAL IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER. POSSIBLE DEVELOPMENTAL HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE ADVERSE DEVELOPMENTAL EFFECTS, BASED ON ANIMAL DATA.

### **Hazardous Material Information System (U.S.A.)** :

|                  |   |   |
|------------------|---|---|
| Health           | * | 2 |
| Flammability     |   | 2 |
| Physical hazards |   | 0 |
|                  |   |   |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### **National Fire Protection Association (U.S.A.)** :



**Date of issue** : 04/30/2011  
**Date of previous issue** : 07/01/2010  
**Version** : 2

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.