

Material Safety Data Sheet

Series 600 DOT 4 Racing Brake Fluid

Section 1. Product and company identification

Product name

Series 600 DOT 4 Racing Brake Fluid

Material uses

Brake fluids.

Supplier/Manufacturer

AMSOIL INC. 925 Tower Avenue Superior, WI 54880 Code BF4 MSDS authored by AMSOIL INC. In case of emergency CHEMTREC: (800) 424-9300

Section 2. Hazards identification

Emergency overview		
Color	priess to yellow.	
Physical state	id. [Fluid.]	
Odor	er.	
Signal word	RNING!	
Hazard statements	ISES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HA WALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORG 1AGE, BASED ON ANIMAL DATA.	
Precautions	not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and only with adequate ventilation. Keep container tightly closed and sealed use. Wash thoroughly after handling.	
OSHA/HCS status	material is considered hazardous by the OSHA Hazard Communication S CFR 1910.1200).	tandard
Potential acute health effects		
Inhalation	ting to respiratory system. Exposure to decomposition products may caus ard. Serious effects may be delayed following exposure.	e a health
Ingestion	be harmful if swallowed.	
Skin	ting to skin.	
Eyes	ting to eyes.	
Potential chronic health effect		
Chronic effects	tains material that may cause target organ damage, based on animal data	
Carcinogenicity	nown significant effects or critical hazards.	
Mutagenicity	nown significant effects or critical hazards.	
Teratogenicity	nown significant effects or critical hazards.	
Developmental effects	nown significant effects or critical hazards.	
Fertility effects	nown significant effects or critical hazards.	
Target organs	tains material which may cause damage to the following organs: upper res , skin, central nervous system (CNS), eye, lens or cornea.	piratory

Over-exposure signs/symptoms

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: No specific data.
Skin	: Adverse symptoms may include the following: irritation redness
Eyes	: Adverse symptoms may include the following: pain or irritation watering redness
Medical conditions aggravated by over- exposure	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.
•	

See toxicological information (Section 11)

Section 3. Composition/information on ingredients

United States		
Name	CAS number	<mark>%</mark>
2-Aminoethanol	141-43-5	10 - 30
Triethylene glycol monomethyl ether	112-35-6	0.1 - 1
Canada		
Name	CAS number	<mark>%</mark>
2-Aminoethanol	141-43-5	10 - 30

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

Eye contact	: Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.
Skin contact	: After contact with skin, wash immediately with plenty of soap and water. Get medical attention if symptoms occur.
Inhalation	: Move exposed person to fresh air. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call medical doctor or poison control center immediately.
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Section 5. Fire-fighting measures

Flammability of the product	:	No specific fire or explosion hazard.
Extinguishing media		
Suitable	:	Use an extinguishing agent suitable for the surrounding fire.
Not suitable	4	None known.

Hazardous decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions Environmental precautions	Put on appropriate personal protective equipment (see Section 8). Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods for cleaning up		
Small spill	orb with an inert dry material and place in an appropriate was	te disposal container.
Large spill	vent entry into sewers, water courses, basements or confined an effluent treatment plant or proceed as follows. Contain an combustible, absorbent material e.g. sand, earth, vermiculite place in container for disposal according to local regulations oose of via a licensed waste disposal contractor. Contaminate pose the same hazard as the spilled product. Note: see sec fact information and section 13 for waste disposal.	nd collect spillage with or diatomaceous earth (see section 13). ed absorbent material

Section 7. Handling and storage

Handling	: Put on appropriate personal protective equipment (see Section 8). Avoid contact with used product. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Empty containers retain product residue and can be hazardous. Do not reuse container.
Storage	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

United States

Ingredient	Exposure limits	
2-Aminoethanol	ACGIH TLV (United States, 2/2010). STEL: 15 mg/m ³ 15 minute(s). STEL: 6 ppm 15 minute(s). TWA: 7.5 mg/m ³ 8 hour(s). TWA: 3 ppm 8 hour(s). NIOSH REL (United States, 6/2009). STEL: 15 mg/m ³ 15 minute(s). STEL: 6 ppm 15 minute(s). TWA: 8 mg/m ³ 10 hour(s). TWA: 3 ppm 10 hour(s).	

	OSHA PEL (United States, 6/2010). TWA: 6 mg/m ³ 8 hour(s). TWA: 3 ppm 8 hour(s).	
--	---	--

Canada

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)			Ceiling				
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
2-Aminoethanol	US ACGIH 2/2010 AB 4/2009 BC 9/2010 ON 7/2010 QC 6/2008	3 3 3 3 3 3	7.5 7.5 - 7.5 7.5		6 6 6 6	15 15 - 15 15	- - -	- - - -	- - - -	- - -	[3]

[3]Skin sensitization

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	Personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
Engineering measures	:	No special ventilation requirements. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Hygiene measures	:	Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.
Respiratory	:	Not required under normal conditions of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure an MSHA/NIOSH-approved respirator or equivalent is used.
Hands	:	Use gloves appropriate for work or task being performed. Recommended: Natural rubber (latex).
Eyes	:	Safety eyewear should be used when there is a likelihood of exposure. Recommended: Safety glasses with side shields.
Skin	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. No special protective clothing is required. Recommended: Coveralls.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Section 9. Physical and chemical properties

Physical state	: Liquid. [Fluid.]	Odor	: Ether.
Color	: Colorless to yellow.	рН	: 7
Flash point	: Closed cup: 146.1°C (295°F) [Pensky- Martens.]	Auto-ignition temperature	: Not available.
Flammable limits	: Not available.	Melting point/ Pour point	: <-59°C (<-74.2°F)
Boiling point	: 361.8°C (683.2°F)	Vapor pressure	: <0.0013 kPa (<0.01 mm Hg) [20°C]
Relative density	: 1.08	Vapor density	: Not available.
Volatility	: Not available.	Evaporation rate	: Not available.
Viscosity	: Kinematic: 0.02 cm ² /s (2 cSt) (100°C) Kinematic: 10.65 cm ² /s (1065 cSt) (40°C)	Solubility	: Not available.

Section 10. Stability and reactivity

Chemical stability Conditions to avoid	 The product is stable. No specific data.
Materials to avoid	: Reactive or incompatible with the following materials: oxidizing materials, acids and
	alkalis.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
2-Aminoethanol	LD50 Oral	Rat	1720 mg/kg	-
Chronic toxicity	No specific data.		•	

Section 12. Ecological information

Environmental effects Aquatic ecotoxicity	: Not established		
Product/ingredient name	Result	Species	Exposure
2-Aminoethanol	Acute LC50 >100000 ug/L Marine water Acute LC50 170000 ug/L Fresh water	Crustaceans - Crangon crangon - Adult Fish - Carassius auratus - 3.3 g	48 hours 96 hours

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. This material and its container must be disposed of in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Empty containers or liners may retain some product residues. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

DOT/TDG/IMDG/IATA : Not regulated.

Section 15. Regulatory information

United States	
HCS Classification	: Irritating material Target organ effects
U.S. Federal regulations	: United States inventory (TSCA 8b): Not determined.
	 SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: 2-Aminoethanol; Triethylene glycol monomethyl ether SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Aminoethanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard; Triethylene glycol monomethyl ether: Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

<u>SARA 313</u>

Form R - Reporting	Product name	CAS number	Concentration
requirements	Triethylene glycol monomethyl ether	112-35-6	0.1 - 1
Supplier notification	: Triethylene glycol monomethyl ether	112-35-6	0.1 - 1

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.


State regulations	
Massachusetts	: The following components are listed: 2-Aminoethanol
New York	: None of the components are listed.
New Jersey	: The following components are listed: 2-Aminoethanol; Triethylene glycol monomethyl ether
Pennsylvania	: The following components are listed: 2-Aminoethanol; Triethylene glycol monomethyl ether
California Prop. 65	
No products were found.	
<u>Canada</u>	
WHMIS (Canada)	: Class D-2B: Material causing other toxic effects (Toxic).
Canadian lists	 CEPA Toxic substances: None of the components are listed. Canadian ARET: None of the components are listed. Canadian NPRI: None of the components are listed. Alberta Designated Substances: None of the components are listed. Ontario Designated Substances: None of the components are listed. Quebec Designated Substances: None of the components are listed.

Canada inventory : Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations	
International lists	: Australia inventory (AICS): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory: Not determined.
	Korea inventory: Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.

Section 16. Other information



Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.