



Synthetic Marine Gear Lube

High-Performance Lubricant Engineered to Meet the Demands of Marine Applications

AMSOIL Synthetic Marine Gear Lube is an exclusive AMSOIL formulation of synthetic base oils and high-performance additives that addresses the specific concerns of marine applications. It is fortified with extreme-pressure (EP) additives for superior protection of fast-accelerating, high-torque/horsepower engines. It protects against shock loading from cavitation of heavily loaded engines.

AMSOIL Synthetic Marine Gear Lube is water resistant. It maintains extreme-pressure protection even when contaminated with as much as 10 percent water. It promotes longer seal life to help prevent water contamination. AMSOIL Synthetic Marine Gear Lube is designed to prevent rust and is compatible with aluminum, copper and brass alloys.



75W/80W-90

Extreme-Pressure and Foam-Stability Testing		
Test	AMSOIL Synthetic Marine Gear Lube	
	No Water	With 10% Water
FALEX Extreme-Pressure Load Test B (LbF) (ASTM D3233B)	2000	2000
Foam Stability (ASTM D892)		
Sequence I	0/0	0/0
Sequence II	0/0	0/0
Sequence III	0/0	0/0

- **Excellent** gear and bearing protection, even when contaminated with 10 percent water
- **Reduced** friction and wear
- **Protects** against rust and corrosion
- **Long** seal life
- **Superior** foam prevention

Marine gear oils operate in environments subject to water contamination. The chart above demonstrates the ability of AMSOIL Synthetic Marine Gear Lube to maintain designed qualities such as extreme-pressure/anti-wear performance and resistance to foaming, even when subjected to 10 percent water contamination.

The Falex Procedure is a measurement of a gear lube's extreme-pressure and anti-wear properties. A high value in the Falex Extreme-Pressure Test relates to extra extreme-pressure protection. AMSOIL Synthetic Marine Gear Lube provides extreme-pressure protection and is highly resistant to the effects of water contamination.

The presence of foam in a lubricant disrupts oil film and promotes wear. Water contamination can increase the likelihood of foaming. Industry standard testing demonstrates zero foam in both new and water-contaminated AMSOIL Synthetic Marine Gear Lube.

TYPICAL TECHNICAL PROPERTIES

AMSOIL Synthetic Marine Gear Lube 75W/80W-90 (AGM)

Kinematic Viscosity @ 100°C, cSt (ASTM D445)	15.4
Kinematic Viscosity @ 40°C, cst (ASTM D445)	117.3
Viscosity Index	137
Flash Point, °C (°F) (ASTM D92) 150°C Min.	208 (406)
Pour Point, °C (°F) (ASTM D97)	-43 (-45)
Falex Procedure B (ASTM D3233) (failure load, LbF)	2000
Foam Stability (ASTM D892) (20/50/20 maximum)	0/0/0

Applications

AMSOIL Synthetic Marine Gear Lube is recommended for fresh- and salt-water applications requiring either 75W-90 or 80W-90 viscosity grade and meeting either API GL-4 or GL-5 performance standards.

Engineered for use in applications that require a 75W/80W-90 marine gear lube, including the following: **Outboard lower units:** Mercury*/Mariner*, Johnson*/Evinrude*, Bombardier*, Honda*, Yamaha*, Suzuki*, Force*/US Marine*, Nissan*, Tohatsu*, Harbormaster Marine*. **Outboard Drives:** Sears Gamefisher* and Seagull*. **Sterndrives:** Mercruiser-Bravo*, OMC*/Bombardier*, Volvo-Penta*, Yanmar*, Konrad Marine Drive Systems*. **V-Drives:** Casale & Menkens*. **Bow & tunnel thrusters:** Harbormaster Marine*. **Marine Transmissions:** ZF Marine Transmission*.

COMPATIBILITY

AMSOIL Synthetic Marine Gear Lube is compatible with other commercially available conventional and synthetic marine gear lubes.

Follow manufacturers' recommended service intervals.

It is generally a good idea to change gear lube at the end of a season prior to storage.

AMSOIL PRODUCT WARRANTY

AMSOIL products are backed by a Limited Liability Warranty. For complete information visit www.amsoil.com/warranty.aspx.

HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available via the Internet at www.amsoil.com or upon request at (715) 392-7101. **Keep Out of Reach of Children.** Don't pollute. Return used oil to collection centers.

*All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use. All products advertised here are AMSOIL-engineered for use in the applications shown.



Jeff Fisher
866-292-4700
www.SyntheticOils.us

AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.