



Motorcycle Octane Boost

Maximizes Power and Efficiency

AMSOIL Motorcycle Octane Boost (MOB) increases octane for maximum power and efficiency. It is designed to improve startup performance and eliminate engine ping or knock for increased power at low-rpm operation. Motorcycle Octane Boost contains detergents that help combustion chambers and fuel delivery systems maintain cleanliness for optimum performance. At the recommended treat rate, it does not harm catalytic converters or oxygen sensors and is compatible with all other AMSOIL fuel additives.

Maximizes Power & Performance

When treated at 1.3 oz. per gallon of fuel, Motorcycle Octane Boost increases the octane of gasoline up to three numbers. Increased octane improves power and can eliminate performance-robbing and potentially damaging engine knock or ping (see reverse).

Improves Low-rpm Performance

Engine knock is especially noticeable in some motorcycles during idle or low-rpm operation and high-temperature driving. Most modern bikes are equipped with sophisticated knock-detection systems that can alter spark timing and the air-to-fuel mixture until knock ceases. Although these systems protect the engine from damage, they can also cause reduced horsepower and poor low-rpm operability. AMSOIL Motorcycle Octane Boost helps reduce the need for knock-detection systems to compensate, ensuring maximum low-rpm power and performance in modern bikes.

Cleans Harmful Deposits

Because Motorcycle Octane Boost contains active detergents, it can help maintain the cleanliness of combustion chambers and fuel delivery systems for improved efficiency. For clean up, however, AMSOIL recommends treating gasoline with AMSOIL Quickshot®, which contains a greater concentration of cleaning agents.




What is engine knock and why does it matter?

The tendency of a hydrocarbon fuel, such as gasoline, to knock is measured by its octane number. Lower numbers denote a greater knock tendency; higher numbers denote greater knock control. "Engine knock" is a reference to the sound made from an uncontrolled and early ignition of fuel in the combustion chamber. It causes a knocking or pinging sound, robs the engine of power and can cause catastrophic engine damage. Knock may be eliminated by increasing the fuel's octane.

What is Research Octane Number?

Research Octane Number (RON), Motor Octane Number (MON) and Anti-Knock Index (AKI) are the three most common octane ratings. AKI, the rating with which most North American motorists are familiar, is typically displayed on gas pumps as the average of the fuel's RON and MON $[(R+M)/2]$. RON, however, is the most common industry rating. Therefore, AMSOIL uses the RON rating when conducting performance tests and product validation. Gasoline's RON generally is a few numbers higher than the AKI posted on the gas pump (e.g. 87 octane fuel, or regular pump gas, has a RON of about 91-92).

AMSOIL Motorcycle Octane Boost Increases Research Octane up to 3 Numbers



When marketing their products, some additive manufacturers have adopted a points system where 10 points equals one octane number. A claim that an additive increases octane 30 points translates into an increase of three octane numbers. This approach is often used only to artificially strengthen marketing claims and is not endorsed by AMSOIL.

Treat Rate

One 4-oz. bottle of AMSOIL Motorcycle Octane Boost treats four to six gallons of gasoline. Slight overtreatment causes no issues, but significant overtreatment is not recommended.

APPLICATIONS

Motorcycle Octane Boost is primarily recommended for use in four-stroke air- or liquid-cooled motorcycles manufactured by Harley-Davidson®, Yamaha®, Honda®, Ducati®, BMW®, Triumph® and all other four-stroke motorcycles. It may be used in off-road applications, including ATVs, UTVs and snowmobiles, as an alternative to AMSOIL DOMINATOR® Octane Boost.

Note: Clean spills immediately using a clean towel. If left standing, Motorcycle Octane Boost can stain painted or metal surfaces. If cleaned immediately, there is no need for concern.

HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Material Safety Data Sheet (MSDS). An MSDS is available via the Internet at www.amsoil.com or upon request at (715) 392-7101. **Keep Out of Reach of Children.** Don't pollute.

For AMSOIL warranty information, visit www.amsoil.com/warranty.aspx.



AMSOIL products and Dealership information are available from your local AMSOIL Dealer.

Jeff Fisher

866-292-4700

www.SyntheticOils.us