



Product One Voice Q&A

Product: Heavy-Duty Degreaser (ADG)

Product Area: Heavy Duty

Created: 05/24/2013

Published Date: 06/24/2013

1. Question:

What is AMSOIL Heavy-Duty Degreaser (ADG)?

Answer:

AMSOIL Heavy-Duty Degreaser (ADG) is a fast acting, industrial degreaser designed to remove oil, tars, petroleum-based grime and sticky materials. The concentrated d'limonene chemistry makes Heavy-Duty Degreaser an excellent cleaner for a variety of equipment and surfaces without the environmental and health issues associated with 100% solvent based degreasers.

Question:

- 2.** Is Heavy-Duty Degreaser a better product to use for tools, engine exteriors and garage floors than AMSOIL Power Foam?

Answer:

Yes. Power Foam is designed to clean the interior induction system and carburetor/injectors of engines. AMSOIL Heavy-Duty Degreaser should be used to degrease exterior surfaces of tools, engines and garage/shop floors.

3. Question:

What are the applications for AMSOIL Heavy-Duty Degreaser?

Answer:

AMSOIL Heavy-Duty Degreaser cleans and degreases a full range of metal surfaces found in heavy-duty equipment, powersports equipment, farm equipment, industrial equipment etc. It is an excellent degreaser and cleaner for concrete floors. Heavy-Duty Degreaser may also be used to remove stubborn adhesives.

4. Question:

What is the package size?

Answer:

Heavy-Duty Degreaser is offered in a 15 oz. spray can and in cases of 12 cans per case.

5. Question:

Are there any environmental or regulatory concerns using this product?

Answer:

AMSOIL Heavy-Duty Degreaser can be sold in all of the 50 United States.

6. Question:

How much Heavy-Duty Degreaser should be used?

Answer:

Make sure to coat the soiled area completely. Let the Heavy-Duty Degreaser penetrate the oil and grime for 1-2 minutes. Wipe off residue and repeat if necessary.

7. Question:

Can Heavy-Duty Degreaser be used on painted surfaces, plastics or chrome?

Answer:

AMSOIL Heavy-Duty Degreaser is a powerful cleaner and should not be used on plastic surfaces such as Lexan®, ABS and Noryl. It may degrade poly type clear coatings on painted surfaces or in some rare cases, remove paint. If uncertain, check with the manufacturer or test on a small area before using. Any overspray on these surfaces should be wiped off immediately and will not cause any issues.

Jeff Fisher

866-292-4700

www.SyntheticOils.us